



SUPER 70 MTL

**MANUAL TRANSMISSION LUBE
SPECIAL RACE FORMULATION**

SAE 70

1 US Quart (9.36 ML)

Part# 052-450070

14.99



SynMax Racing Synthetic, Manual Transmission and Trans Axle Lubricant Product Information:

- SynMax™ Manual Transmission and Synchronesh Transaxle Lube (viscosity typical SAE 70).
- SAE30 Hi-Performance Manual transmission, Synchronesh Fluid applications up to 600 HP.
- Transaxle Sportscar or Continental / Atlantic up to 400 HP.
- Diamond Like Additive™ (DLA) & SynMax™ anti-wear technology and synthetic chemistry, protects gears and bearings while greatly reducing parasitic drag; with cooler temperatures and smoother shifting operations.
- Synchronesh fluid formulated products are also created for planetary gear or "straight cut-gear" design applications. This means the lubrication fluid goes into the smallest points of the straight and rolling gear surface areas, while working together with the other synchronesh components etc.
- SynMax Synchronesh fluid type product is a direct cross reference for use as a Manual Transmission Fluid (MTF) with fully synthetic base oil (fluid) is designed specifically for racing, heavy duty and commercial applications. SynMax Synchronesh (MTF) transmission temperatures operate cooler as compared to using a standard gear oil. SynMax Synchronesh (MTF) provides the right balance of protection additives and viscosity stability performance providing reduction in parasitic drag with durability and proven reliability.

Application and Use:

- SAE 70 Manual Transmission Lubricant or trans axle Applications - calling for Synchronesh or Manual Transmission Type Fluid SAE W30 (equal to SAE 70 Gear Lube).
- Hi-Performance manual transmissions for reduced friction and reduced parasitic drag.
- Late Model / Short Track, SCCA or Pro Stock Drag Racing etc.
- Product should be used for suggested and intended design application(s) only.

Features and Benefits

- Aerospace Advantages to increase metal surface technology and component durability through Diamond Like Additive™ (DLA) Technology providing a solid film lubricant with plating action.
- Premium SynMax™ anti-wear formulation. • Protects during short term oil starvation periods.
- Minimizes frictional resistance & gear contact wear. • Proven parasitic drag loss.
- Lower operation temperatures (20°F - 40°F) as compared to other similar type fluids.
- Cooler transmission / transaxle temperatures - provides smoother shifting operations and longer parts life.
- Advanced formulation provides maximum low temperature fluidity as well as high temperature stability.
- Maximizes High temperature/high shear performance protection upon synchronesh, gear, bearing and overall transmission or transaxle components, as fluid and additive formulation flows through the gear and bearing parts, from low to high RPM requirements.
- Seal conditioning, anti-foam and oxidation additives & inhibitors.
- Compatible with all types of Buna seals, other seals & silicone materials.
- Does not include friction modifiers for special clutch material facing requirements.

Copyright 2009 Titan Performance Products, LLC. All Rights Reserved

www.SynMaxPerformanceLubricants.com